

LOADED TIRE SIZE CHART

For use in calculating the mounting height of Silent Drive air suspensions.

Tube Type	Tubeless	ISO (Metric)	Loaded Tire Radius
7.5R15		215/75R17.5	14.0
	8.5R17.5		14.5
8.25R15	9R17.5	225/70R19.5	15.0
	10R17.5	*245/70R19.5	15.5
		*265/70R19.5 *285/70R19.5	16.0
10.00R15			16.5
7.5R20	8R22.5	255/70R22.5 245/75R22.5 235/80R22.5	17.0
			17.5
8.25R20	9R22.5	265/75R22.5 255/80R22.5	18.0
			18.5
9.00R20	10R22.5	295/75R22.5 275/80R22.5	19.0
10.00R20	11R22.5	295/80R22.5 315/80R22.5 385/65R22.5 285/75T24.5 275/80R24.5	19.5
11.00R20	12R22.5		20.0
12.00R20 10.00R22	13R22.5 11R24.5	425/65R22.5	20.5
11.00R22	12R24.5	445/65R22.5	21.0
12.00R22	13R24.5		21.5

* For use only on hub & drum steer axle. Requires special hub piloted wheel, 20" uni-mount drum, and 15" brakes. These tires will not work with 16.5" brakes. Check ground clearance before using these smaller tires.